

JUICEBOX[®] Pro 40

Commercial Charging Stations

Optimize your smart grid EV charging with the best-selling JuiceBox Pro 40

JuiceBox is a Level 2 charging station with all the safety and charging features that cost-conscious businesses and organizations need to maximize their EVSE investments.

Powered by the JuiceNet[®] software platform, JuiceBox offers direct administrator control and smart grid optimization. It offers your customers, employees, and tenants access to best-in-class smart charging solutions and helps you:

- Optimize energy costs by controlling charging times and demand charges
- Conveniently monetize your EV charging
- Increase grid reliability and support EV adoption
- Enhance driver satisfaction and reach sustainability goals



Why JuiceBox?

<p>Powered by JuiceNet</p> <p>Intuitive mobile app for drivers and powerful online dashboard for system administrators</p>	<p>Smart Grid Connected</p> <p>Optimize charging times and aggregate stations to reduce energy costs</p>	<p>Great Performance & Value</p> <p>Best-in-class smart charging station at an affordable price</p>
<p>Universal Compatibility</p> <p>SAE-J1772[™] compliance ensures compatibility with all EVs*</p>	<p>Access Control & Payment</p> <p>With JuiceNet Enterprise software, allow registered drivers to access charging stations via mobile device and pay to charge with the mobile app</p>	<p>Compact & Easy to Use</p> <p>Small enclosure, weatherproof for indoor/outdoor installation, LED charging status indicators</p>

*Tesla requires adapter

JuiceBox® Pro 40 Specifications

Electrical Characteristics

- › Safety Rated: 40A Max
- › Single phase input: nominal voltage 208-240 VAC ~60 Hz
- › Power: 8.3 kW at 208 VAC; 9.6 kW at 240 VAC

Input Cable & Plug

- › 2 ft/0.6 m with NEMA 14-50 or 6-50 plug
- › 2.5 ft/0.8 m hardwire pigtail

Output Cable & Connector

- › 25 ft/7.6 m cable
- › J1772 standard compliant

JuiceNet® Smart Charging Platform

- › Precision measurement of power, energy, voltage & current
- › Web-based portal: set payment rates and charging hours; monitor charging status and consumption data for individual or groups of devices; control station access; manage EV load
- › Driver app to monitor and pay for charging (iOS & Android)
- › Refer to the JuiceNet Business and JuiceNet Enterprise data sheets for more on the capabilities of each dashboard

Connectivity & Authentication

- › WiFi-enabled: 802.11 b/g/n 2.4 GHz
- › Integrated Cellular: LTE (optional)
- › JuiceRouter: Connect up to 16 chargers with WiFi-to-LTE router (optional)
- › RFID enabled and QR Code authenticated with JuicePass Enterprise Mobile App

Firmware

- › End-to-end AES-256-based encrypted protocols
- › 90-day, 15-minute interval data storage
- › Over-the-air (OTA) upgradeable firmware
- › Persistent data storage upon power interruption

Enclosure

- › Dynamic LED lights show charging status: network connectivity, charging in progress, delayed charging, standby, charge complete/EV not drawing power
- › IP66: Weatherproof, dust-tight, polycarbonate enclosure
- › IK10: Resistant polycarbonate case
- › Quick-release wall mounting bracket included
- › Built-in security lock and integrated cable management
- › Operating Temperature: -40°F to 140°F (-40°C to 60°C)

Weight & Dimensions

- › Main enclosure: H: 18.5 in/469 mm x W: 6.8 in/173 mm x D: 5.8 in/147 mm
- › 15 lbs/6.8 kg

Codes & Standards

- › FCC Part 15 Class B, NEC 625 compliant, ENERGY STAR®
- › OCPP 1.6J and Open ADR2.0b compliant
- › ISO 15118 support (optional)

Safety

- › UL and cUL Listed

Warranty

- › 3-year limited parts warranty for commercial use. 2-year warranty extension available

Made in North America

- › From domestic & imported parts

