

JuiceBox® Pro 80

Future-proof your EV charging with Enel X's fastest smart Level 2 station

2 station JuiceBox® Pro 80 is a powerful Level 2 charging station with all the safety and charging features businesses, fleet operators, school districts and transportation agencies need to maximize their electric vehicle investments.

Powered by JuiceNetTM, our smart EV charging platform, JuiceBox, affords both direct user control and smart grid optimization. It offers drivers, customers, employees and tenants access to best-in-class smart charging and helps:

- •Optimize energy costs by controlling charging times and demand charges
- •Conveniently monetize EV charging
- Increase grid reliability and support EV adoption
- •Enhance driver satisfaction and reach sustainability goals



Why JuiceBox Pro?

Powered by JuiceNet

Intuitive mobile app for drivers and powerful online dashboard for system administrators

Smart Grid Connected

Optimize charging times and aggregate stations to reduce energy costs

Universal Compatibility

SAE-J1772TM compliance ensures compatibility with all EVs

Access Control & Payment

With JuiceNet Enterprise software, allow registered drivers to access charging stations via mobile device or RFID card and pay to charge with the mobile app

Future-Proof

Invest in charging stations that will provide ample power even as new EV battery sizes increase

Compact & Easy to Install

Small enclosure, weatherproof for indoor/outdoor installation, LED charging status indicator. A great alternative to more expensive fast chargers.

*Tesla requires adapter



Electrical Characteristics	 Safety rated: 80A Max Single phase input: nominal voltage 110-240 VAC ~50/60 Hz Power: 8.8 kW at 110 VAC; 19.2 kW at 240 VAC
Input Cable	Installer must provide and ensure input cable meets all applicable electrical codes 25 ft/7.6 m cable
Output Cable & Connector	 J1772 standard compliant Precision measurement of power, energy, volume & current
JuiceNet® Smart Charging Platform	 Web-based portal: set rates and charging hours; monitor charging status and consumption data for individual devices or groups of devices; control station access; set payment rates; load management Driver app to monitor and pay for charging (iOS & Android) Refer to the JuiceNet Manager and JuiceNet Enterprise data sheets for more on the capabilities of each dashboard WiFi-enabled: 802.11b/g/n 2.4 GHz
Connectivity & Authentication	Integrated Cellular: LTE (optional) JuiceRouter: Connect up to 16 chargers with WiFi-to-LTE router (optional) RFID enabled and QR Code authenticated with Enel X Way® app End-to-end AES-256-based encrypted protocols 90-day, 15-minute interval data storage
Firmware	 Over-the-air (OTA) upgradeable firmware Persistent data storage upon power interruption Dynamic LED lights show charging status: network connectivity, charging in progress, delaying charging, standby IP66: Weatherproof, dust-tight
Enclosure	 IK10: resistant polycarbonate case Quick-release wall mounting bracket included Built-in security lock and integrated cable management Operating Temperature: -40F to 122F (-40C to 50C) Up to 2000 m/6500 ft Main enclosure: H: 18.5 in/469 mm x W: 6.8 in/173 mm x D: 5.8 in/147 mm
Altitude	→ 17 lbs/7.7 kg
Weight & Dimensions	 FCC Part 15 Class B, NEC 625 compliant, ENERGY STAR®† OCPP 1.6J and Open ADR2.0b compliant UL and cUL certified
Codes & Standards	 3-year limited parts warranty for commercial use. 2-year warranty extension available From domestic & imported parts
Safety	>
Warranty	>

6.8 in/17.3 cm

JUICEBOX and JUICENET are registered trademarks of Enel X North America, an Enel Group company. Other product and company names mentioned herein may be trademarks or trade names of their respective owners.

Varies by model, certifications pending.